

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
7 December 2000 (07.12.2000)

PCT

(10) International Publication Number
WO 00/73676 A1

(51) International Patent Classification⁷: F16F 9/05,
B60G 11/28

Mark, Guy [US/US]; 2203 East Arndale Road, Stow, OH
44224 (US).

(21) International Application Number: PCT/US99/11772

(74) Agent: KRAWCZYK, Nancy, T.; D/823, The Goodyear
Tire & Rubber Company, 1144 East Market Street, Akron,
OH 44316-0001 (US).

(22) International Filing Date: 28 May 1999 (28.05.1999)

(25) Filing Language: English

(81) Designated States (*national*): AL, AM, AT, AU, AZ, BA,
BB, BG, BR, BY, CA, CH, CN, CU, CZ, DE, DK, EE, ES,
FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE,
KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG,
MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE,
SG, SI, SK, SL, TJ, TM, TR, TT, UA, UG, US, UZ, VN,
YU, ZA, ZW.

(26) Publication Language: English

(71) Applicant (*for all designated States except US*): THE
GOODYEAR TIRE & RUBBER COMPANY [US/US];
D/823, 1144 East Market Street, Akron, OH 44316-0001
(US).


(84) Designated States (*regional*): ARIPO patent (GH, GM,
KE, LS, MW, SD, SL, SZ, UG, ZW), Eurasian patent (AM,
AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT,
BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC,

(72) Inventor; and

(75) Inventor/Applicant (*for US only*): TROWBRIDGE,

[Continued on next page]

(54) Title: AIR SPRING UPPER RETAINER



(57) Abstract: An air spring (1) has a cylindrical flexible airsleeve (2) secured at each end to form a fluid chamber (14). One end (6) of the sleeve (2) is secured to a retainer (8). The retainer (8) has a ribbed reinforcement structure (16) which allows the air spring (1) to be directly mounted to a moveable part of a vehicle or other machinery. The retainer (8) has an extending mounting means (13) on one side of the reinforcement structure (16) and a bead seating surface (12) adjacent to the reinforcement structure (16).

WO 00/73676 A1

Best Available Copy



NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

Published:

— *With international search report.*

AIR SPRING UPPER RETAINER

Field of the Invention

The present invention is directed toward a retainer for an air spring. More particularly, the present invention is a thermoplastic upper retainer for an air spring
5 which provides for easy air spring assembly and mounting.

Background of the Invention

Air springs have been used for motor vehicles and various other machines and equipment for a number of years. The springs provide cushioning between movable parts, primarily to absorb shock loads imparted thereon. The air spring consists of at
10 least one flexible elastomeric reinforced sleeve extending between a pair of retainers, forming a pressurized chamber therein. The sleeve typically has a relatively inextensible bead core at each end for securing the sleeve to the retainers. Alternatively, the sleeve may be secured to the retainers by conventional crimping means. There may be one or more pistons associated with the air spring. The retainers also assist in securing the air
15 spring on spaced components or parts of the vehicle or equipment by being secured to a mounting plate which is attached to the moveable part of the vehicle or machine.

The fluid in the pressurized chamber, generally air, absorbs most of the shock impressed upon or experienced by one of retainers. The retainers move towards and away from each other when the air spring is subjected to any forces.

Both upper and lower retainers are conventionally formed of stamped metal. If
20 the air spring has a piston, the piston, upon which the lower retainer is secured, may be metal or thermoplastic. A bumper, mounted on either retainer and provided for impact absorption and transference, is usually thermoplastic or thermoelastic, depending upon the forces which will ultimately be acting on the air spring and the forces to which the
25 bumper will be subjected.

When the air spring is mounted to a vehicle, a subassembly made from coated steel stampings and plumbing components are used to achieve the mounting attachment, air connection and airsleeve bead captivation. Such conventional mounting means are illustrated in the following U.S. patents: 5,203,585; 5,464,245; 5,403,031, and 5,346,247.
30 The present invention provides for a single molded part to achieve all of these functions.

Summary of the Invention

The present invention is directed toward providing a lightweight, low cost means of easily attaching the air supply end of the air spring directly to a suspension frame rail of a vehicle.

The present invention is an improved air spring for absorbing and transmitting shock loads between parts moveable relative to one another. The air spring comprises a flexible cylindrical sleeve which is secured at each end to form a fluid chamber therein. One end of the sleeve is secured to a retainer. The retainer has a ribbed reinforcement structure which allows for direct mounting of the airspring to one of the moveable parts.

The ribbed reinforcement structure of the disclosed retainer is comprised of a plurality of ribs. In an alternative construction, the ribs may run the full length of the reinforcement structure. The ribs may also be at least two sets of ribs, with the ribs extending at different angles relative to each other.

The disclosed retainer has an axially extending mounting plate for directly mounting the air spring to the moveable part.

The disclosed retainer also has a bead seating surface. The bead seating surface is adjacent to the ribbed reinforcement structure.

The disclosed retainer is formed from a thermoplastic material having a tensile strength in the range of 28,000 to 45,000 psi, and a flex strength in the range of 40,000 to 60,000 psi.

Brief Description of the Drawings

The invention will be described by way of example and with reference to the accompanying drawings in which:

FIG. 1 is a half cross-sectional view of an air spring with the inventive upper retainer;

FIG. 2 is a perspective view of the inventive retainer;

FIG. 3 is a side view of the upper retainer;

FIG. 4 is a top view of the retainer;

FIG. 5 is a bottom view of the retainer; and

FIG. 6 is a cross-section view of the retainer through line 6-6 of FIG. 3.

Detailed Description of the Preferred Embodiments

The present invention is illustrated within an assembled air spring 1 in FIG. 1. The air spring 1 has a cylindrical elastomeric sleeve 2. The elastomeric sleeve 2 is preferably comprised of at least 3 plies: an outer elastomeric ply 3, at least one reinforcing ply 4 formed of elastomeric embedded reinforcing cords, and an inner elastomeric ply 5. The upper end 6 of the sleeve 2 has a relatively inextensible bead 7 for securing the airsleeve 2 to the inventive upper retainer 8. The bead core 7 is at least one continuous winding of wire, preferably steel. The configuration of the bead core 7

may vary as is conventionally known. The lower end 9 of the airsleeve 2 may also be defined by a bead core 10 for securing the lower end 9 of the airsleeve 2.

5 The lower end 9 of the airsleeve 2 is secured to a piston 11. The lower end 9 of the airsleeve 2 may be secured in any conventional manner, including, but not limited to, crimping the lower end 9 of the airsleeve 2 to the piston or to a conventional lower retainer or by securing the bead core 10 by a lower retainer. An internal bumper may be provided for absorbing impact forces. When the air spring 1 is in use, the upper retainer 8 moves in an axial direction and the sleeve 2 travels up and down the outside of the piston 10.

10 The inventive upper retainer 8, seen illustrated in FIGS 2 to 6, is a unitary article, provided with both bead seating means 12 and mounting means 13. The underside of the retainer 8 is defined by the bead seating surface 12, see FIG. 3. At the axially innermost edge of the bead seating surface 12, relative to the air chamber 14 formed within the air spring 1, is a bead retention lip 15. The bead retention lip 15 has a radial width of at
15 most 10 mm, and is preferably in the range of 2 mm to 6 mm. The width of the bead retention lip 15 is greater than zero to prevent the bead 7 from dismounting and disengaging from the retainer 8 under low-pressure operation of the air spring 1. If the bead retention lip 15 has a radial dimension greater than 10 mm, then the bead 7 cannot be press-fitted onto the retainer 8 without damage to either the airsleeve 2 or the bead 7
20 due to the highly inextensible nature of the bead. In mounting the bead 7 to the retainer 8, the bead 7 is held onto the retainer 8 by the interference fit between the bead seating surface 12 and the air spring bead 7 to effect a seal. The radius of the bead seating surface 12 is less than the greatest radius of the retainer 8, but greater than the radius of the air spring bead 7.

25 The intermediate reinforcement section 16 of the air spring retainer 8 is defined by a plurality of ribs 17 which extend the length of the retainer 8. The ribs 17 are located between the outer plate 18 and the inner plate 19. A preferred embodiment of the ribs 17 is illustrated in FIGS. 2, 3 and 6. As seen most clearly on FIG. 6, the ribs 17 extend the full length of the outer and inner plates 18,19. The ribs 17 are substantially equal in
30 width and are equidistant from each other, forming equiwidth cavities. The ribs 17 are blended at the point of connection with the upper and lower plates 18,19. Also between the two plates 18,19 are two ribs 20 which extend perpendicular to the plurality of ribs 17. These perpendicular ribs 20 assist in providing structural support to the retainer 8.

As noted, the illustrated configuration is the preferred embodiment for the structural ribbing and air inlet means of the upper retainer 8. The ribbing 17, 20 between the upper and lower plates 18, 19 is provided for structural integrity and impact resistance. The distance between the ribs 17, and thus the relative widths of the cavities, may vary in accordance with the resulting impact forces to which the air spring 1 will be subjected. Both the ribbing 17 and perpendicular ribbing 20 may extend from either the top plate 18 or the bottom plate 19 without contacting the opposing plate. Additionally, all of the chambers may be formed with a more circular cross-section and more rounded radially inner end points than presently illustrated. The ribbing may also be provided in other configurations wherein the ribbing extends at angles relative to one another, such as in a herringbone or diamond pattern, to vary the retainer strength characteristics. The configuration of the ribbing pattern is limited solely by molding dictates.

Two adjacent air chambers 21 provide means for the flow of the pressurized fluid into and out of the pressurized chamber 14. The chambers 21 are formed with a smaller width and a lesser extending depth than the formed cavities. At the radially inner most point 22 of the fluid admitting chambers 21, the chambers 21 terminate in an orifice 23 which extends through the bottom plate 19. The stepped-in configuration of the fluid admitting chambers 21 permit a push-in fitting to be secured in the retainer 8 during a post molding action. The walls of the fluid admitting chambers 21 are shaped to match the configuration of the push-in fittings. The orifice 23 may extend through the retainer 8 in an axial direction only, as opposed to the illustrated radial/horizontal access for fluid flow. For such a construction, the entire intermediate section 16 of the retainer 8 is defined by ribbing 17, 20 and two axial extending orifices for the insertion of air fittings pass through both the upper and lower plates 18, 19.

On the axially outer side of the top plate 18, means 13 are provided for securing the air spring 1 to any vehicle frame or bracket upon which it is desired to mount the air spring 1. A unitary plate 24 is located off-centered on the top plate 18. The location of the plate 24, relative to the center of the top plate 18, as well as the height and width of the plate 24 is dependent on the vehicle frame structure on which the air spring 1 is to be mounted. The plate 24 is supported by a set of braces 25. The plate 24 and the braces 25 are formed as an integral part of the retainer 8 by molding the plate 24 with the retainer 8, welding the plate 24 to the retainer 8, or by bonding the plate 24 to the retainer 8; the plate 24 is preferably molded as an integral part of the retainer 8. The plate 24 is

provided with at least one mounting hole 26. The holes 26 are reinforced with steel inserts 27 to strengthen the mounting of the air spring 1.

5 The retainer 8 is injection molded from a resilient material, preferably thermoplastic. Examples of applicable material include, but are not limited to, fiberglass reinforced nylon, long fiber reinforced thermoplastic, commercially available as
CELSTRAN, and short fiber reinforced thermoplastic, commercially available as
ZYTEL. The tensile strength of the material should be within the range of 28,000 to
45,000 psi, have a flex strength in the range of 40,000 to 60,000 psi, and notched izod
strength of 2.0 to 12.0 ft-lb/in.

10 Variations in the present invention are possible in light of the description of it
provided herein. While certain representative embodiments and details have been shown
for the purpose of illustrating the subject invention, it will be apparent to those skilled in
this art that various changes and modifications can be made therein without departing
from the scope of the subject invention. It is, therefore, to be understood that changes
15 can be made in the particular embodiments described which will be within the full-
intended scope of the invention as defined by the following appended claims.

CLAIMS

1. An improved air spring (1) for absorbing and transmitting shock loads between parts moveable relative to one another, the air spring (1) comprising a flexible cylindrical sleeve (2) which is secured at each end to form a fluid chamber (14) therein, the sleeve (2) being secured at one end (6) to a retainer (8), the improvement being characterized by:
the retainer (8) having a ribbed reinforcement structure (16) allowing for direct mounting of the airspring (1) to one of the moveable parts.
2. An improved air spring (1) in accordance with claim 1 wherein the ribbed reinforcement structure (16) comprises a plurality of extending ribs (17 or 20).
3. An improved air spring (1) in accordance with claim 2 wherein the ribs (17 or 20) extend the full length of the reinforcement structure (16).
4. An improved air spring (1) in accordance with claim 1 wherein the ribbed reinforcement structure (16) comprises at two sets of ribs (17 or 20) extending at angles relative to each other (20 or 17).
5. An improved air spring (1) in accordance with claim 1 wherein the retainer (8) has an axially extending mounting plate (24) for directly mounting the air spring (1) to the moveable part.
6. An improved air spring (1) in accordance with claim 1 wherein the retainer (8) is formed from a thermoplastic material having a tensile strength in the range of 28,000 to 45,000 psi, and a flex strength in the range of 40,000 to 60,000 psi.
7. An improved airspring (1) in accordance with claim 6 wherein the retainer (8) is formed from a material selected from the following group: fiberglass reinforced nylon, long fiber reinforced thermoplastic, and short fiber reinforced thermoplastic.

8. An improved air spring (1) in accordance with claim 1 wherein the retainer (8) is comprised of a bead seating surface (12), the bead seating surface (12) being located adjacent the ribbed reinforcement structure (16).
- 5 9. An improved air spring (1) in accordance with claim 1 wherein the retainer (8) is comprised of air inlet means (21, 23) which extend through the ribbed reinforcement structure (16).


$\frac{1}{4}$ 

FIG- 1

2/4




FIG-2




FIG-3

3/4




FIG-4




FIG-5

4/4




FIG-6

INTERNATIONAL SEARCH REPORT

International Application No

PCT/US 99/11772

A. CLASSIFICATION OF SUBJECT MATTER

IPC 7 F16F9/05 B60G11/28

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 7 F16F B60G

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
Y	US 5 326 082 A (ROBBINS MATTHEW A ET AL) 5 July 1994 (1994-07-05) figures 1,2 ---	1,2,7
Y	US 5 535 994 A (SAFREED JR CARL K) 16 July 1996 (1996-07-16) the whole document ---	1,2,7
A	US 4 733 876 A (HEIDER DALE J ET AL) 29 March 1988 (1988-03-29) figures 5,6 ---	1,2,5
A	PATENT ABSTRACTS OF JAPAN vol. 009, no. 055 (M-362), 9 March 1985 (1985-03-09) & JP 59 190533 A (SUMITOMO DENKI KOGYO KK), 29 October 1984 (1984-10-29) abstract --- -/--	1,6,7

☒ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

* Special categories of cited documents:

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier document but published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

"&" document member of the same patent family

Date of the actual completion of the international search

10 January 2000

Date of mailing of the international search report

17/01/2000

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo rd,
Fax: (+31-70) 340-3016

Authorized officer

Tsitsilonis, L

INTERNATIONAL SEARCH REPORT

International Application No

PCT/US 99/11772

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT		
Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	EP 0 306 040 A (TAURUS GUMIIPARI VALLALAT) 8 March 1989 (1989-03-08) figure 5 ---	1,8
A	US 2 977 134 A (HELLING, J.) 28 March 1961 (1961-03-28) figures 2-4 ---	1,9
A	US 3 790 147 A (OWEN R) 5 February 1974 (1974-02-05) figure 2 ---	1,9
A	EP 0 123 171 A (FIRESTONE TIRE & RUBBER CO) 31 October 1984 (1984-10-31) figures 1-3 ---	1
A	EP 0 295 392 A (FIRESTONE TIRE & RUBBER CO) 21 December 1988 (1988-12-21) figure 1 ---	1
A	EP 0 590 317 A (BRIDGESTONE FIRESTONE INC) 6 April 1994 (1994-04-06) figure 1 ---	1
A	US 5 467 971 A (HURTUBISE DIANE M ET AL) 21 November 1995 (1995-11-21) column 5, line 17 - line 63; figures -----	

INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/US 99/11772

Patent document cited in search report		Publication date	Patent family member(s)		Publication date
US 5326082	A	05-07-1994	JP	6026544 A	01-02-1994
US 5535994	A	16-07-1996	CA	2117051 A	31-05-1995
US 4733876	A	29-03-1988	CA	1273967 A	11-09-1990
JP 59190533	A	29-10-1984	NONE		
EP 0306040	A	08-03-1989	HU	207382 B	29-03-1993
			AT	75530 T	15-05-1992
			CS	8805857 A	12-09-1990
			DE	3870550 A	04-06-1992
			HR	931014 A	30-04-1996
			SI	8811623 A,B	30-04-1996
			SU	1642959 A	15-04-1991
			US	5024424 A	18-06-1991
US 2977134	A	28-03-1961	FR	1210944 A	11-03-1960
			GB	847324 A	
US 3790147	A	05-02-1974	NONE		
EP 0123171	A	31-10-1984	US	4564177 A	14-01-1986
			AU	585749 B	22-06-1989
			AU	1469888 A	21-07-1988
			AU	574068 B	30-06-1988
			AU	2632284 A	25-10-1984
			BR	8401847 A	27-11-1984
			CA	1216601 A	13-01-1987
			DE	3475216 A	22-12-1988
			JP	1829024 C	15-03-1994
			JP	5031691 B	13-05-1993
			JP	59200831 A	14-11-1984
			MX	159175 A	27-04-1989
			NZ	207730 A	06-03-1987
EP 0295392	A	21-12-1988	US	4787606 A	29-11-1988
			AU	606414 B	07-02-1991
			AU	1534288 A	22-12-1988
			CA	1307799 A	22-09-1992
			DE	3864453 A	02-10-1991
			JP	2825494 B	18-11-1998
			JP	63318334 A	27-12-1988
EP 0590317	A	06-04-1994	US	5342139 A	30-08-1994
			BR	9303958 A	05-04-1994
			CA	2107247 A	31-03-1994
			DE	69322465 D	21-01-1999
			DE	69322465 T	29-04-1999
			JP	6193619 A	15-07-1994
US 5467971	A	21-11-1995	NONE		

**This Page is Inserted by IFW Indexing and Scanning
Operations and is not part of the Official Record**

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ BLACK BORDERS
- ☐ IMAGE CUT OFF AT TOP, BOTTOM OR SIDES
- ☒ FADED TEXT OR DRAWING
- ☐ BLURRED OR ILLEGIBLE TEXT OR DRAWING
- ☐ SKEWED/SLANTED IMAGES
- ☐ COLOR OR BLACK AND WHITE PHOTOGRAPHS
- ☐ GRAY SCALE DOCUMENTS
- ☐ LINES OR MARKS ON ORIGINAL DOCUMENT
- ☐ REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY
- ☐ OTHER: _____

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.